

511

PTFE LUBRICANT



Description

- Dry lubricant for deck hatch slides, drawers, and pulley axis.
- Lubrication of clothing zippers, bags, etc ...
- Not greasy, dries quickly.

Product information

Composition	EC 927-510-4 HYDROCARBONS, C7,N- ALKANES, ISOALKANES, CYCLIC EC 931-254-9 HYDROCARBONS, C6, ISOALKANES, <5% N-HEXANE, EC 227-006-8 TÉTRABUTANOLATE DE TITANE
Appearance/ Odour	Liquide fluid-aerosol / odor-free
pH	N.A
Density	<1
Flash point	N.A
Transport N° ONU	1950
Storage	Store between + 5 ° C. and + 30 ° C. in a dry, well ventilated place, away from sources of ignition.
Packaging	200ml aerosol

Directions for use

Compatibility / supports	All materials: wood, leather, metal, plastic, rubber, etc.
Méthodes	<ul style="list-style-type: none"> - Shake before use. - Spray at about 20/30 cm from the previously cleaned surface. Avoid applying too much product . - Drying time: 15 to 30 minutes. - Drain the can always head down for a few seconds after use to clean the spray nozzle

Precautions for use

- Danger. Extremely flammable aerosol.



Danger



Danger



Pollutant

Extremely flammable aerosol. Pressurized container: May burst if heated. Causes skin irritation. Causes serious eye irritation. Before use: Shake the can. Always carry out a test on a small surface. After each use: Purge the aerosols nozzle.

**SAFETY DATA SHEET
AVAILABLE ON REQUEST**

Always refer to the descriptions on labels. Keep out of reach of children. Respect the conditions of use.